

2025 Volkswagen ID. Buzz Technical Specifications

| Technical Specifications | | ID. Buzz RWD | | ID.Buzz | AWD | | |
|---|---------|--|---|--|---|-------------------------------|--|
| MOTOR | | | | | | | |
| Type front | | _ | | ASM asynch | nronous | | |
| Type rear | | PSM permanent magnet synchror | nous | PSM perma | nent magnet s | synchronous | |
| System Horsepower, hp (SAE) | | 282 | | 335 | | | |
| Torque, lb-ft | | 413 | | 99(front) / 4 | 413(rear) | | |
| BATTERY & ELECTRICAL | | | | | | | |
| High Voltage Battery, Type | | Lithium-ion | | Lithium-ion | <u> </u> | | |
| High Voltage Battery Capacity, Gross | | 91 kWh | | 91 kWh | • | | |
| High Voltage Battery Capacity, Net | | 86 kWh | | 86 kWh | | | |
| AC Onboard Charger, Maximum Acceptance Rate | | 11 kW | | 11 kW | | | |
| DC Maximum Acceptance Rate | | 200 kW | | 200 kW | | | |
| Number of cells | | 208 | | 208 | | | |
| Maximum Voltage | | 442 V | | 442 V | | | |
| Battery Assembly Weight (lb) | | 1230 | | 1230 | | | |
| DRIVETRAIN | | | | | | | |
| Driven wheels | | Rear-wheel drive | | All-wheel d | lrive | | |
| Diver wheels | | Automatic | | Automatic | | | |
| Transmission Gear Ratios:1 | | Rear | | Rear | Front | | |
| Hallstillssion deal Ratios.1 | 1st | 2.52 | | 2.52 | 3.00 | | |
| | Reverse | 2.52 | | 2.52 | 3.00 | | |
| | Final | 3.90 | | 3.90 | 3.78 | | |
| STEERING | | | | | | | |
| | | Electric rack-and-pinion | | Electric rac | k-and-pinion | | |
| Type Turns (lock to lock) | | 3.42 | | 2.95 | k-and-pinion | | |
| Turning Circle (curb to curb) | | 3.42 37.4 ft / 11.4 m | | 42.7 ft / 13 | 0 m | | |
| Ratio | | 14.6.1 | 15.0:1 | | | | |
| INTERIOR VOLUME - SAE | | 11.0.1 | | 13.0.1 | | | |
| | | NI I OMB | | | 15 | | |
| EPA Class | | Minivan 2WD | Minivan 2WD 7 | | Minivan 4WD | | |
| Seating Capacity Passenger Volume w/o glass roof (cu ft) | | 160.1 | | 160.1 | | | |
| Passenger Volume w/ glass roof (cu ft) | | 163.7 | | 163.7 | | | |
| Cargo Volume (behind 1st row) (cu ft) | | 145.5 | | 145.5 | | | |
| Cargo Volume (behind 2nd row) (cu ft) | | 75.5 | | 75.5 | | | |
| Cargo Volume (behind 3nd row) (cu ft) | | | 18.6 | | 18.6 | | |
| cargo volume (Berlina Sha Tow) (ca 11) | | 1st row 2nd row 3rd ro | nw. | 1st row | 2nd row | 3rd row | |
| Volume w/o glass roof (cu ft) | | 52.1 58.4 49.6 | | 52.1 | 58.4 | 49.6 | |
| Volume w/ glass roof (cu ft) | | 53.9 60.3 49.6 | | 53.9 | 60.3 | 49.6 | |
| Headroom w/o glass roof (in/mm) | | 40.6/1032 41.0/1042 38.7/9 | 982 | 40.6/1032 | 41.0/1042 | 38.7/982 | |
| Headroom w/ glass roof (in/mm) | | 42.0/1067 42.3/1074 38.7/9 | 982 | 42.0/1067 | 42.3/1074 | 38.7/982 | |
| Shoulder Room (in/mm) | | 59.1/1502 61.7/1567 52.2/2 | 1326 | 59.1/1502 | 61.7/1567 | 52.2/1326 | |
| Hip Room (in/mm) | | 58.1/1476 64.8/1645 48.2/2 | 224 | 58.1/1476 | 64.8/1645 | 48.2/1224 | |
| Legroom (in/mm) | | 37.5/952 39.9/1013 42.4/ | 1076 | 37.5/952 | 39.9/1013 | 42.4/1076 | |
| BODY, CHASSIS AND SUSPENSION | | | | | | | |
| Туре | | Unitary Construction | | Unitary Cor | struction | | |
| Body Material | | | Steel | | Steel | | |
| Front Suspension | | Strut-type with lower control arm | Strut-type with lower control arms, coil | | | | |
| • | | • • | springs, telescopic dampers, anti-roll bar | | springs, telescopic dampers, anti-roll bar | | |
| Rear Suspension | | Multilink with coil springs, telesco | Multilink with coil springs, telescopic | | Multilink with coil springs, telescopic | | |
| | | dampers, anti-roll bar | | | dampers, anti-roll bar | | |
| Brakes | | | 15.0 x 1.2-in vented front discs and 13.0 x | | | | |
| Anti-Lock Braking System | | 2.0-in rear drums | 2.0-in rear drums Standard, all four wheels | | 2.0-in rear drums | | |
| <u> </u> | | | | Standard, all four wheels Standard Electronic Stability Control (ESC) | | | |
| Stability Control Parking Prake | | Standard Electronic Stability Control (ESC) Electro-mechanical | | Standard Electronic Stability Control (ESC) Electro-mechanical | | | |
| Parking Brake | | | | | | | |
| Wheels/Tires | | 8J x 20 aluminum-alloy wheels | 235/50 R20, all-season tires | | 8J x 20 aluminum-alloy wheels 235/50 R20, all-season tires | | |
| | | | 9.5J x 20 aluminum-alloy wheels in rear | | 9.5J x 20 aluminum-alloy wheels in rear | | |
| | | | - | | | R20, all-season tires in rear | |
| Drag Coefficient | | 0.29 | uı | 0.29 | o, un ocason li | ico in ical | |
| Drag Coemicient | | V.L / | | 0.27 | | | |



2025 Volkswagen ID. Buzz

| Technical Specifications | ID. Buzz RWD | ID.Buzz AWD | |
|---|--------------|-------------|--|
| DIMENSIONS | | | |
| Wheelbase (in/mm) | 127.5/3239 | 127.5/3239 | |
| Front Track (in/mm) | 65.8/1672 | 65.8/1672 | |
| Rear Track (in/mm) | 65.7/1670 | 65.7/1670 | |
| Length (in/mm) | 195.4/4962 | 195.4/4962 | |
| Width w/o mirrors (in/mm) | 78.1/1985 | 78.1/1985 | |
| Height (in/mm) | 76.2/1935 | 76.2/1935 | |
| Approach Angle (degrees) | 17.5 | 17.5 | |
| Departure Angle (degrees) | 19.5 | 19.5 | |
| Breakover Angle (degrees) | 13.6 | 13.6 | |
| Ground Clearance (in/mm) . | 6.3/161 | 6.3/161 | |
| WEIGHTS | | | |
| Curb Weight NHTSA (lb/kg) | 5968/2707 | 6197/2811 | |
| GVWR (lb/kg) | 7408/3360 | 7408/3360 | |
| Payload (lb/kg) | 1113/505 | 948/430 | |
| Towing Capacity, Unbraked (lb/kg) | 1650/748 | 1650/748 | |
| Towing Capacity, Braked (lb/kg) | 2600/1179 | 3500/1588 | |
| CONSUMPTION | | | |
| City (MPGe) | 90 | 87 | |
| Highway (MPGe) | 75 | 74 | |
| Combined (MPGe) | 83 | 80 | |
| Electric Consumption, Combined (kWh/100 mi) | 41 | 42 | |
| Range (EPA mi) | 234 | 231 | |

Specifications, equipment, options, and prices are subject to change without notice